Dynapac CC3200C

Combi rollers





Technical data

Masses	
Max. operating mass	8,700 kg
Operating mass (incl. ROPS)	7,700 kg
Module mass (front/rear)	4,075/3,625 kg

(i)	Fraction	
9	Speed range (Dual/TC/AS)	0-12 km/h
\	/ertical oscillation	±7
7	Theor. gradeability	45 %

Compaction	
Wheel load	906 (kg/wheel)
Centrifugal force (high/low amplitude)	90/75 kN
Nominal amplitude (high/low)	0.7/0.3 mm
Static linear load	23.6 kg/cm
Vibration frequency (high/low amplitude)	48/67 Hz
Water tank	750 I
Emulsion tank	781

Engine		
Manufacturer/Model	Deutz TCD 3.6 IIIB/T4i	
Туре	Water cooled turbo Diesel with After Cooler	
Rated power, SAE J1995	75 kW (100 hp) @ 2,200 rpm	
Fuel tank capacity	130 I	

Engine		
Manufacturer/Model	Cummins QSB 3.3 IIIA/T3	
Rated power, SAE J1995	74 kW (99 hp) @ 2,200 rpm	


Hydraulic system	Hydraulic system	
Driving	Axial piston pump with variable displacement. Axial piston motors (3) with variable displacement.	
Vibration	Axial piston pump with variable displacement. Axial piston motor with constant displacement.	
Steering	Gear pump with constant displacement.	
Service brake	Hydrostatic in forward and reverse lever.	
Parking/ Emergency brake	Failsafe multidisc brake in both drums.	


Dynapac CC3200C

Combi rollers



Technical data





Dimensions	
A. Wheelbase	3,340 mm
B. Width	1,870 mm
C. Curb clerance	715 mm
D. Drum diameter	1,150 mm
H1. Height, with ROPS/cab	2,990 mm
H2. Height, w/o ROPS/cab	2,275 mm
K. Ground clearance	270 mm
L. Length	4,490 mm
R. Turning radius, outside	5,266 mm
S. Drum shell thickness	18 mm
W1. Drum width	1,730 mm
W2. Width, wheel module	1,652 mm
W3. Width, tyre	285 mm
W4. Wheel track	467 mm
W5. Wheel spacing	165 mm
α. Steering angle	±32°