

# OFF ROAD Construction F28

**F28**  
55 kW (74 HP) @ 2500 rpm  
Stage V / Tier 4 Final

## SPECIFICATIONS

No. of cylinders / valves	4L / 2	
Aspiration	WG (TCA)	
Injection System	COMMON RAIL (up to 1600 bar)	
Displacement	liters	2.8
Bore per Stroke	millimeters	91 x 108
Max power	kW (HP) @ rpm	55 (74) @ 2500
Peak torque	Nm (kgm) @ rpm	375 (-) @ 2500
ATS	DOC (Tier4F) / DOC - DPF (Stage V)	
Certification	Stage V / Tier 4 Final	

## WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	623 x 580 x 750
Dry Weight	Kg	250

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS

## POWER & TORQUE



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

**CONSTRUCTION**

Do you want to know more?



### LEGEND

#### Air Handling

- TC (Turbocharged)
- NA (Naturally Aspirated)
- TCA (Turbocharged with aftercooler)

#### Turbocharger

- WG (Wastegate)
- VGT (Variable Geometry Turbocharger)
- TST (Twin Stage Turbocharge)

#### Exhaust System

- EGR (Exhaust Gas Recirculation)
- SCR (Selective Catalytic Reduction)
- DPF (Diesel Particulate Filter)
- DOC (Diesel Oxidation Catalyst)

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE [WWW.FPTINDUSTRIAL.COM](http://WWW.FPTINDUSTRIAL.COM)

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE

