



**strautmann**



Manure spreader

CS-spreader



# CS-spreader

## – Compact and flexible

The CS spreader is the successor model of the BE spreader which has proven itself over decades. The compact CS spreader is particularly suitable for businesses with in-house mechanisation and ensures effective discharge of manure. The folding side panels enable a double use as a transport trailer.

4-beater spreading unit ensures an optimum spreading pattern at an operating width of up to 8 m

Robust protection strips prevent damage to the side panels



Folding side panels for flexible charging

## Robust design for strong performance



### Transport floor

- Reliable feed by one (CS 75) or two (CS 95) transport floor lines
- 10 mm strong round steel chains with a breaking load of 13 t each
- Screwed transport floor strips
- 25 mm thick wooden floor



### 4-beater spreading unit

- Four upright spreading beaters for operating widths between 6-8 m
- Fan-shaped spreading tines ensure even crushing of the spreading material
- Powered via low-maintenance gearboxes



### Chassis

- Single axle or spring-loaded tandem chassis (CS 95) for maximum driving comfort
- Various tyre options



#### Side panel and extensions

- Folding to reduce the charging height
- Flexibility due to double use as a transport trailer
- 400 mm high extension panels optionally available to increase the loading capacity



#### Transport floor drive

- High-torque feed gearing with hydraulic drive
- Infinitely variable adjustment of feed rate by means of control valve on the drawbar



#### Grouping of lubrication points

- Optional lubricating strip for upper spreading beater bearings
- Easy and convenient maintenance

# Technical data

	CS 75 with 520/50 R 17 tyres	CS 95 with 520/50 R 17 tyres
<b>Dimensions</b>		
Length [m]	6,16	6,96
Height [m]	2,84	2,88
Outside wheel width [m]	2,17	2,17
Charging height [m]	1,75	1,79
<b>Dead weight</b>		
Dead weight from [kg]	2.000	2.300
<b>Gross vehicle weight rating</b>		
Gross vehicle weight rating from [kg]	5.700	8.000
<b>Power required</b>		
Power required from [kW/HP]	26/35	37/50
<b>Inside dimensions of superstructure</b>		
Length [m]	3,70	4,60
Width [m]	1,80	1,80
Side panel height [m]	0,50	0,50
<b>Loading capacity</b>		
Loading capacity [m <sup>3</sup> ]	7,5	9,5
<b>Spreading unit</b>		
Spreading unit clearance [m]	1,15	1,15

Figures, technical data and weights may change due to technical development and are not binding for delivery.





[www.strautmann.com](http://www.strautmann.com)

**B. Strautmann & Söhne GmbH u. Co. KG**



Bielefelder Straße 53  
D-49196 Bad Laer  
Tel.: +49(0)5424/802-0  
Fax: +49(0)5424/802-76  
[info@strautmann.com](mailto:info@strautmann.com)