





HW 90B/10 / HW 90B/12

HW 90B/10 - Static three-wheel roller
HW 90B/12 - Static three-wheel roller



- Two ergonomic driver seats
- Hydrostatic drive
- 2 weight classes: 10-12 t, can be loaded to 12-14 t
- ldeal load distribution between front and rear drum
- Water pressure sprinkler, electronically controlled
- Large water tank with 400 I long application time
- 4-cylinder turbo-engine
- Comprehensive range of special accessories



HW 90B/10 - Static three-wheel roller HW 90B/12 - Static three-wheel roller



HW 90B/10 HW 90B/12 Weights 10670 Operating weight kg 12465 Maximum weight kg 14000 4090/6580 16000 5115/7350 Axle load, front/rear kg Static linear load, front/rear kg/cm 37,2/53,9 46,5/60,2 Machine dimensions 2020 2365 Max. working width mm 2020 2365 Turning radius, inside mm Diesel engine DFUT7 DFUT7 Manufacturer TD 2011 L04 I TD 2011 L04 I Type Number of cylinders Power rat. ISO 14396, kW/HP/rpm 56,5/76,8/2500 56,5/76,8/2500 Power rating SAE J1349, kW/HP/rpm 56,5/75,7/2500 56,5/75,7/2500 Emission standard EU / USA III / Tier 3 III / Tier 3 Drive Hydrostatic drive, front/rear -/planetary gear -/planetary gear Speed, infinitely variable 0 - 10,2 km/h 0 - 10,2 Climbing ability, with/no ballast % 25/40 25/40 Steering Pivot steering, front Pivot steering, front Steering, type Steering, actuation hydrostatic, steering wheel hydrostatic, steering wheel Steering angle +/-40 Oscillation angle +/-8 8 Brake system Service brake, mode hydrostatic hydrostatic Service brake, actuation Drive lever Drive lever Spring-loaded/mechanical Spring-loaded/mechanical Parking brake, mode Parking brake, actuation electr. a. autom. electr. a. autom. Emergency brake, mode hydr./mech. hydr./mech.

Equipment

Spring-mounted driver seat, 2 comfort seats, Automatic starter interlock, Operating hours counter, ROPS comfortable spacious cab, Lighting per German Road Traffic Regulations, Speedometer, CE conformity

Emergency stop

interval/manual

Pressure

400

Emergency stop

interval/manual

HW 90B/10 / HW 90B/12 # 913901 ENGB01 - Further data on request / subject to change

Pressure

400

Optional equipment

Χh

Emergency brake, actuation

Sprinkler system
Water sprinkler, type

Actuation, sprinkling

Water tank, capacity

ROPS comfort cab, 360°-glazing, Exterior and interior mirrors, Electric fan, Heating with dust-free ventilation, Rotating beacon, Seat belt, Sound insulation, Sunroof, Edge pressing and cutting equipment, Tilting axle, Hydraulic differential lock, Coir mats

Total length	L	4890	4890	
Width	В	2020	2020	
Total height	H	3220	3220	
Wheel base	Α	2830	2830	
Drum width, front	Χv	1100	1100	
Drum diameter, front	Dv	1250	1250	
Drum width, rear	Xh	610	610	
Drum diameter rear	Dh	1550	1550	

