

S 60 | 80 PLUS



- **COMPACT WHEELBASE**
- **EXCLUSIVE PATENTED TRANSMISSION WITH THE “DUAL POWER” SYSTEM**
- **DRIVING COMFORT: PLATFORM ON “SILENT BLOCK” AND “OVERVIEW” CAB WITH A/C**
- **EXCELLENT WEIGHT/POWER RATIO AND WEIGHT DISTRIBUTION**
- **TYPE-APPROVED TO 40 KM/H**

Even more advanced

Starting with this Series, we have worked to further develop its strengths, adding a host of more advanced, comprehensive features: the S 60 and the S 80 are two machines that boast all the power you need, combined with the unrivalled agility and reliability that characterise all Goldoni products. It is the perfect choice for those working in the specialised crop sector who don't want to compromise on cutting-edge equipment and performance.

TECHNICAL FEATURES

ENGINE

VM 3 Cyl - 43 kW / 58 HP / 4 Cyl 55 kW 75 HP

Tier IIIB Turbo

Direct injection

TRANSMISSION

Dual Power 16+8, 8+8 transmission with lateral levers

Mechanical Reverse Shuttle

4WD and Mechanical DIFF-lock

HYDRAULIC

Lifting capacity 2300 kg

Pump output 38 l/min, open-centre

3 rear mechanical distributors

DRIVER AREA

Integrated platform/cab on silent-block suspension

DIMENSIONS

Wheelbase: 1690-1831 mm

Weight: 1900 kg (platform)

Tyre: 360/70R20

Width (min-max): 1290-1766 mm