

Platform

0.76 m x 1.83 m low mount platform
 Side entry with inward swing gate
 Multiple function operation
 Full proportional drive joystick control with integral thumb steer switch
 Full proportional main boom and swing joystick control
 Variable speed dial control for telescope and platform rotate
 Selectable creep speed on drive / lift and swing functions
 180 degree powered platform rotator
 Platform console machine status light panel ¹
 Load sensing system
 AC cable to platform

Functional Equipment & Accessories

4 degree tilt alarm and indicator light
 12 x 16.5 foam filled lug tread tyres
 Fixed-width frame (extending axles not required)
 Lifting/tie down lugs
 Hour meter
 Ground control selector switch with key lock
 Platform tool tray
 12V DC auxiliary power

¹ Provides indicator lights at platform control console for system distress, low fuel, tilt light, and foot switch status.
² Low oil pressure and high coolant temperature alarms with shut-down enabled/disabled by analyser.
³ Available when integrated with the SkyPower™ package.
⁴ Available only with two wheel drive on models 400S and 460SJ.
⁵ Includes all-motion alarm and flashing amber beacon.
⁶ Includes platform mounted work lights and head & tail lights.
⁷ Includes console cover, boom wipers and cylinder bellows.

Available Options

0.91 m x 1.83 m low mount platform
 0.91 m x 2.44 m low mount platform
 13 mm air line to platform
 Four wheel drive
 12 x 16.5 foam filled non marking tyres
 14 x 17.5 foam filled lug tread tyres
 Semi-track package (includes floating idler system)
 Oscillating front axle
 On-board 2500W Generator
 SkyPower™ Package 7,500 watt on-board generator
 SkyWelder® Package 250 amp welder in the platform ³
 Tow Package ⁴
 All motion alarm
 Alarm package ⁵
 Light package ⁶
 Head and tail lights
 Flashing amber beacon
 Plugs & Sockets
 Hostile environment package ⁷
 Catalytic Purifier Muffler
 Soft Touch Proximity System
 Corner storage tray

Power & Transmission

Perkins 404C-22 (37 kW) diesel engine
 Engine distress warning/shut down system ²
 Gull-wing hoods
 Swing-out engine tray
 Spark arresting type muffler
 Control ADE™ - Advanced Design Electronics System
 Hydrostatic drive transmission
 Horn

JLG Industries Inc.
 Polaris Avenue 63
 2132 JH Hoofddorp
 The Netherlands
 Tel: +31 (0)23 565 5665
 Fax: +31 (0)23 557 2493
 e-mail address: europe@jlg.com
www.jlgeurope.com
 An Oshkosh Corporation Company

Printed in UK
 FORM No.: DS034-0208-500
 PART NO.: DS034-ENGLISH



400S

Platform height	12.29 m
Horizontal outreach	10.39 m
Swing (continuous)	360°
Platform capacity – unrestricted	230 kg
Optional platform capacity	340 kg
Platform rotator (hydraulic)	180°
Jib – overall length	—
Jib - range of articulation	—
A. Platform size	0.76 m x 1.83 m
B. Overall width	2.30 m
C. Tailswing (working condition)	0.86 m
D. Stowed height	2.39 m
E. Stowed length	7.54 m
F. Wheelbase	2.34 m
G. Ground clearance	0.32 m
Machine weight ¹	6,200 kg
Maximum ground bearing pressure	4.07 kg/cm ²
Maximum tyre load	3,230 kg
Drive speed 2WD	7.2 km/h
Drive speed 4WD	7.2 km/h
Gradeability 2WD	30%
Gradeability 4WD	45%
Tyres	12 x 16.5 Foam Filled
Axle oscillation (optional)	0.20 m
Turning radius – inside	2.01 m
Turning radius – outside	5.00 m
Diesel engine Perkins 404C-22	37 kW
Diesel engine (option) CAT C2.2	37 kW
Fuel tank capacity	98 L
Hydraulic system	197 L
Auxiliary power	12V DC

¹ Certain options or country standards may increase weight and/or dimensions.

