

Platform

- 0.91 m x 2.44 m low mount platform
- Side entry with inward swing gate
- Multiple function operation
- Full proportional drive joystick control with integral thumb steer switch
- Full proportional main boom and swing joystick control
- Variable speed dial control for telescope and platform rotate
- 2.44 m articulating jib
- JibPLUS® with 4 way axis jib including 180 degree horizontal motion
- Powered side stow on jib
- 180 degree powered platform rotator
- Platform console machine status light panel ¹
- Load sensing system
- AC cable to platform

Functional Equipment & Accessories

- Selectable dual platform capacity system (230kg/450kg)
- Drive-out extending axles
- 5 degree tilt alarm and indicator light
- 445/50D710 foam filled lug tread tyres
- Oscillating front axle
- Lifting/tie down lugs
- Hour meter
- Ground control selector switch with key lock
- Load sensing hydraulics
- Platform tool tray
- 12V DC auxiliary power

Available Options

- 0.91 m x 1.83 m low mount platform
- 13 mm air line to platform
- Engine distress warning/shut down system ²
- On-board 2500W generator
- SkyPower™ package 7,500 watt on-board generator
- SkyWelder® package 250 amp welder in the platform ³
- SkyGlazier TM package glass and panel tray
- Nite-Bright® package ⁴
- All motion alarm
- Alarm package ⁵
- Light package ⁶
- Flashing amber beacon
- Plugs & Sockets
- Hostile environment package ⁷
- Catalytic purifier muffler
- Soft Touch proximity system
- Corner storage tray

Power & Transmission

- Deutz TD2011L04 (56 kW) diesel engine
- Gull-wing hoods
- Swing-out engine tray
- Spark arresting type muffler
- Control ADE™ (Advanced Design Electronics) System
- Adjustable swing drive
- Hydrostatic transmission
- Four wheel drive
- Four wheel steer/two wheel steer/crab steer
- Horn

JLG Industries Inc.

Polaris Avenue 63
2132 JH Hoofddorp
The Netherlands
Tel: +31 (0)23 565 5665
Fax: +31 (0)23 557 2493
e-mail address: europe@jlg.com
www.jleurope.com
An Oshkosh Corporation Company

1200SJP

Platform height	36.73 m
Horizontal outreach	22.86 m
Swing (continuous)	360°
Platform capacity – restricted	450 kg
Platform capacity – unrestricted	230 kg
Platform rotator (hydraulic)	180°
Jib – overall length	2.44 m
Jib - range of articulation	130° Vertical (+75°/-55°)
JibPLUS™ - range of articulation	180° Horizontal
A. Platform size	0.91 m x 2.44 m
B. Overall width (axles retracted)	2.49 m
Overall width (axles extended)	3.81 m
C. Tailswing (working condition)	1.68 m
D. Stowed height	3.05 m
E. Stowed length	10.64 m
F. Wheelbase	3.81 m
Ground clearance	0.30 m
Machine weight ¹	18,500 kg
Maximum ground bearing pressure	7.03 kg/cm ²
Drive speed	5.2 km/h
Gradeability	45%
Tyres	445/50D710 Foam Filled
Axle oscillation	0.30 m
Turning radius – inside (axles retracted)	4.39 m
Turning radius – inside (axles extended)	2.44 m
Turning Radius – outside (axles retracted)	6.86 m
Turning Radius – outside (axles extended)	5.89 m
Diesel engine - Deutz TD2011L04	56 kW
Fuel tank capacity	117 L
Hydraulic system	365 L
Auxiliary power	12V DC

¹ Certain options or country standards may increase weight and/or dimensions.

