

			TM3185F3		
			Manual steering	Power steering (U type)	
			with TY3160F1E	with TY3160F1E	
Dimension	Overall length	(mm)	2,450		
	Overall width	(mm)	1,105		
	Overall height	(mm)	2,250		
	Wheel base	(mm)	1,270		
	Weight (without operator)	(kg)	545	555	
Engine	Model		IHI E673L -D		
	Engine output	Gross	(kW {PS})	11.8 {16.0}	
		Net	(kW {PS})	11.6 {15.8}	
	Number of cylinder		3		
	Displacement	(L)	0.761		
	Revolution	(min-1)	2,700		
	Max torque	Gross	(N·m/min-1)	45.4/2000	
		Net	(N·m/min-1)	44.5/2000	
	Combustion Chamber		Swirl chamber		
Fuel tank capacity	(L)	14			
Transmission	Gear	Main	F3/R1		
		Sub	2		
	Number of Gear		F6/R2		
PTO	Mid PTO		None		
	Rear PTO	Number of Gear	1		
		Speed (min-1)	540		
Rear Axle	Brake		Wet disc		
	Brake Pedal Type		Two pedals		
	Parking Brake		Lever type		
	Diff-lock		Std. (Pedal)		
	Max. Speed	Forward	(km/h)	18.8	
Reverse		(km/h)	10.3		
Front Axle	Type		4WD, 2WD		
	Steering		Manual steering	Hydraulic power steering	
	Front Bumper		Opt.		
	Front Hitch		Std.		
Hydraulic	3-point linkage	@ link end	(kgf)	540	
		@ 24inch behind	(kgf)	280	
	3-point linkage control		Position Control		
	Aux. Valve		Opt.		
Electric	Power terminal of beacon lamp		Std.		
Exterior	Floor		Semi Flat		
	Floor Mat		Std.		
	Seat		Std.		
	Rear-view mirror		Std. (LH & RH) /Opt.		
ROPS	Rear ROPS		Std. /Opt.		
	Type		Foldable		
EU Homologation	Homologation Category		(EU) No. 167/2013		